CHARACTER BROADCASTING RECEIVING SET

Publication number: JP5236437

Publication date:

1993-09-10

Inventor:

KURODA KAZUO; HASEBE TAKESHI

Applicant:

PIONEER ELECTRONIC CORP

Classification:

- international:

H04N5/445; H04N7/025; H04N7/03; H04N7/035; H04N7/088; H04N5/445; H04N7/025; H04N7/03:

H04N7/035; H04N7/087; (IPC1-7): H04N7/08;

H04N5/445

- European:

H04N7/088P

Application number: JP19920031047 19920218 Priority number(s): JP19920031047 19920218

Also published as:

US5373324 (A1) GB2264426 (A)

Report a data error here

Abstract of JP5236437

PURPOSE:To improve operability in the case of selecting the program of character broadcasting by executing correspondent program display when the display contents of characters displayed at a display position designated by a display position input means correspond to a program number. CONSTITUTION:TV radio waves desired to be received are tuned by a tuner 2, and signals for character broadcasting superimposed on 14H (H:horizontal period)-16H and 21H in the vertical flyback periods of outputted intermediate video frequency signals are sampled by a sampling circuit 3 and stored in a RAM 5 as display code data after correcting error at an error correction circuit 4. A controller 9 stores data for display in a memory 6 for display by referring to the display code data in the RAM 5 and a character memory 8 and displays pictures on a display 7. The controller 9 detects the coordinates of a mouse as a pointing device 10 and decides an executing processing from the obtained coordinate of the mouse. When the display contents correspond to the program number of a certain program, the controller 9 displays the correspondent program.

